



MILTECH™ 402

Rugged PoE Ethernet Switch with Power Distribution Capabilities

FEATURES DESCRIPTION

The MILTECH™ 402 Rugged POE Ethernet Switch with Power Distribution Capabilities provides constant LAN & Power between multiple devices used by infantry Soldiers. This MIL-STD, Rugged POE Ethernet Switch with Power Distribution Capabilities features 5 LAN 10/100 (Fast Ethernet) ports + Power supply for each port.

With a voltage range of 10-16.8VDC, from a military battery pack, the MILTECH™ 402 supplies 2 LAN channels with PoE (15.4 watt each), 2 LAN channels with 16.8 Vdc/5A (Vbat) & 1 LAN channel with 5V/1.5A.

MILTECH™ 402 features mechanical packaging enhancements designed for MIL-STD-810F airborne and ground environmental compliance and high reliability. The unit has been especially

hardened to improve ingress, impact, and shock/vibration protection. Passive cooling allows for the elimination of moving parts. Sealed connectors ensure protection against water and dust.

This flexible Network & Power platform creates another superior lightweight & flexible solution for Future Soldier applications in the modern battlefields. The MILTECH™ 402 is well suited to provide LAN + Power while packed in combat vests for infantry soldiers. It extends Our commitment to unique, tailor-made SWAP rugged communications solutions.

SPECIFICATIONS

ETHERNET PORTS	<ul style="list-style-type: none"> Total of 5 Ethernet 10/100 (Fast Ethernet) ports + Power Supply: 2 x PoE, 10/100 (Fast Ethernet) ports 1 x 10/100 (Fast Ethernet) port + 5V/1.5A Power Supply 2 x 10/100 (Fast Ethernet) port + 10V -16.8V/5A (Vbat) Power Supply
NETWORKING	<ul style="list-style-type: none"> Full wire-speed forwarding rate Store-and-forward mechanism Auto MDI-II, MDI-X Auto-Negotiation Protocol Address Look-Up
CONNECTORS	<ul style="list-style-type: none"> Power Connector: SCE2-B-76A -10ASN LAN/PoE Connectors: SCE2-B-76A06-075N PAN1 Connector: SCE2-B-76A06-075N PAN2,3 Connectors: SCE2-B-76A-145N Indication Per Port (Link/Activity, Speed, PoE) On/Off Switch Dark Mode
CHASSIS	<ul style="list-style-type: none"> Machined rugged aluminum Conductively cooled w/custom internal heat-sinks Ingress protection against sand, dust and moisture Anodize Coating, MIL-A-8625, Type II, Class
STANDARDS	<ul style="list-style-type: none"> MILSTD-461E MILSTD-810F GM IP67





MILTECH™ 402

Rugged PoE Ethernet Switch with Power Distribution Capabilities


SPECIFICATIONS

PERFORMANCE	<ul style="list-style-type: none"> • 26.8 Mpps wire speed forwarding rate • 20 Gbps maximum forwarding bandwidth • 8K MAC Address • Wire-Speed Reception and Transmission • Integrated Address Look-Up Engine • Automatic Address Learning
STANDARDS COMPLIANCE	<ul style="list-style-type: none"> • IEEE 802.3 10 Mbps 10BASE-T (Ethernet) • IEEE 802.3u 100BASE-TX 100 Mbps (Fast Ethernet) • IEEE 802.3x Flow Control
POWER	<ul style="list-style-type: none"> • Voltage Input: 10VDC – 16.8VDC Battery Supply • Power Consumption: 140W maximum • Chassis grounding • Over Current Protection 1.5A & 5A. • Overload, Over-Voltage & Short Circuit Protection for PoE Ports. • Reverse Polarity Protection
PoE	<ul style="list-style-type: none"> • Total PoE Budget 35W • Maximum Consumption per port 15.4W • Dynamic Power Allocation • PoE Priority per port • Full Comply to IEEE 802.3af • No Power Degradation at +85°C • Operates from Regular Military 10-16.8VDC Smart Battery Supply (4 cell Li-ion)
ELECTROMAGNETIC	<ul style="list-style-type: none"> • Design to meet: MIL-STD-461E Electromagnetic compatibility • CE-102 CS-114 CS-115 CS-116 RE-102 RS-103
SHOCK/VIBRATION/HUMIDITY	<ul style="list-style-type: none"> • Design to meet: MILSTD-810F/G/GM: • Random vibration (514.5I) Bench Handling (516.6VI) High Temp.(501.5I,II) Low Temp.(502.5I) Humidity (507.5II) Air Pressure (500.5I,II) Blowing Rain (506.5I) Immersion (512.5I) Salt Atmosphere (509.5I) Blowing Dust (510.5I) Loose Cargo Vibration (514.6II) Wind Analysis. • IP67
PHYSICAL	<ul style="list-style-type: none"> • Dimensions: 100mm (L) x 94.2mm(W) x 34.1mm(H), including connectors & hardware • Dimensions: 3.93”(L) x 3.7”(W) x 1.34”(H), including connectors & hardware • Weight: 280gr
INSTALLATION	<ul style="list-style-type: none"> • Set of Four 4x40 mounting holes on bottom for mounting to any flat surface • Option for Strap Mounting Bracket
COOLING	<ul style="list-style-type: none"> • No Moving Parts. Passive Cooling.
OPERATING TEMP	<ul style="list-style-type: none"> • -40°C to +85°C (-40°F to +185°F) - Cold Start-Up
STORAGE TEMP	<ul style="list-style-type: none"> • -45°C to +85°C (-49°F to +185°F)



MILTECH™ 402

Rugged PoE Ethernet Switch with Power Distribution Capabilities



ORDERING INFORMATION

PART NUMBER	DESCRIPTION
1-402-000	5 x 10/100 Fast Ethernet Switch + PoE & Power Supply
800-A402-00	Strap Mounting Bracket
2-CBL402PWR	Power cable for MILTECH402
2-CBL402PAN1	PAN1 LAN+POWER Cable for MILTECH402
2-CBL402PAN2/3	PAN2/3 LAN+POWER Cable for MILTECH402
2-CBL402LANP	LAN/PoE cable for MILTECH402
2-CBL402LANP+	LAN/PoE + Management cable for MILTECH402