

## STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4366 Series datasheet, detailing the specific features and parameters of this variant of the M4366 Series power supplies.

**SERIES: M4366**

**CONFIGURATION: M4366-101**

### ***ELECTRICAL SPECIFICATIONS:***

Input	Outputs					
	VS1	VS2	VS3	+12_Aux	-12_Aux	3.3_Aux
18-48V <sub>DC</sub>	12V/30A	3.3V/20A	5V/30A	N/A	N/A	5A

### ***SPECIAL FEATURES:***

- Passive Current share for VS1, VS2, VS3
- VITA 46.11 System Management
- Support 16V Transients per Mil-STD-1275E
- Works-through 100V Transients




**Cham, Switzerland**  
[www.enercon-europe.com](http://www.enercon-europe.com)  
[enercon@enercon-europe.com](mailto:enercon@enercon-europe.com)  
 +41-41-740-4554

**Global Headquarters**

**Netanya, Israel**  
[www.enercon.co.il](http://www.enercon.co.il)  
[sales@enercon.co.il](mailto:sales@enercon.co.il)  
 +972-73-246 9200



**Gurgaon, India**  
[www.mpsindia.in](http://www.mpsindia.in)  
[sales@mpsindia.in](mailto:sales@mpsindia.in)  
 +91-124-651 0010