ENERCON TECHNOLOGIES LTD

STANDARD CONFIGURATION CATALOG PAGE

This document is an addendum to the M4465 Series datasheet, detailing the specific features and parameters of this variant of the M4465 Series power supplies.

SERIES: M4465
CONFIGURATION: M4465-103

ELECTRICAL SPECIFICATIONS:

Input	Outputs					
	VS1	VS2	VS3	+12_Aux	-12_Aux	3.3_Aux
15-48V_{DC}	12V/30A	3.3V/20A	5V/30A	12V/1A	-12V/1A	3.3V/5A

SPECIAL FEATURES:

- Turn on Voltage below 15V
- Startup time less than 200mSec after applied of proper Input voltage.
- Working through Mil-STD-704F transients
- Support up to 300W at Input voltage lower than 21V.
- Compatible to work as a backend module in conjunction with the M4060 Holdup Module
- 46.11 compatible communication

Note: Specifications are subject to change without prior notice by the manufacturer.

NON ITAR

AS9100D CERTIFIED ISO 9001

ENERCON TECHNOLOGIES LTD
Cham, Switzerland
www.enercon-europe.com
enercon@enercon-europe.com
+41-41-740-4554

Global Headquarters

Netanya, Israel
www.enercon.co.il
sales@enercon.co.il
+972-73-246 9200

MULTISPHERE POWER SOLUTIONS PVT. LTD.
Gurgaon, India
www.mpsindia.in
sales@mpsindia.in
+91-124-651 0010